

Section 1 ~ Identification

Identity (As Used On Label and List) K29 (A1006) MEGA OFF	Date Prepared: 01/14/26	Date Revised: 02/26/26
Company Information: KAYLINE COMPANY, INC.	Emergency Telephone Number: 1-800-424-9300	
Address (Number, Street, Suite/Apt#) 3303 LAKESIDE AVENUE	Telephone Number for Information: 1-800-426-5820	
(City, State, and Zip Code) CLEVELAND, OH 44114	Signature of Prepare (Optional) REGULATORY DEPT.	

Section 2 ~ Hazard(s) Identification

Classifications

Aerosols Category 1
Skin Irritant: Category 2
Eye Irritant: Category 2A
Carcinogenicity: Category 2
Skin Sensitization: Category 1
Specific Target Organ Toxicity (Repeated Exposure): Category 2
Aspiration Hazard: Category 1

Label Elements



Signal Word: DANGER

Hazard Statement

Extremely flammable aerosol. Pressurized container: may burst if heated. Causes skin and serious eye irritation. Suspected of causing cancer. May cause an allergic skin reaction. May cause damage to auditory system through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Precautionary Statement

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No Smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn even after use. Protect from sunlight. Do not expose to temperature exceeding 50°C/ 122°F. Obtain, read and follow all safety instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapors/spray. Do not eat, drink, or smoke when using this product. Wash hands thoroughly after handling. Wear protective gloves, protective clothing, and eye protection. IF ON SKIN: wash with plenty of water. If skin irritation or rash occurs: Get medical help. Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical help. IF EXPOSED OR CONCERNED: get medical advice. IF SWALLOWED: Get emergency medical help immediately. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

Other Hazards

N/A

Unknown acute toxicity (GHS US)

N/A

Section 3 ~ Composition/Information on Ingredients

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Xylene	1330-20-7	10-30%
Acetone	67-64-1	10-30%
Diethylene glycol n-butyl ether	112-34-5	10-30%
Propane	74-98-6	5-10%
n-Butane	106-97-8	5-10%
d-Limonene	5989-27-5	1-5%

Trade Secret Information: A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Section 4 ~ First Aid Measures

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Seek medical attention if irritation persists
INGESTION: Rinse mouth out with water. Do not induce vomiting unless directed by medical authority. Keep head below hips if vomiting occurs. Seek immediate medical attention. Aspiration hazard. Never give anything by mouth to an unconscious person.

INHALATION: Move to fresh air. If irritation or other symptoms develop, seek medical attention.

SKIN: Immediately wash with soap and water for 15 minutes. Continue rinsing skin as needed. Seek medical attention if rash or irritation persists. Take off contaminated clothing and wash it before reuse.

ACUTE HEALTH HAZARDS: Causes skin and serious eye irritation. May be fatal if swallowed and enters airways.

CHRONIC HEALTH HAZARDS: Suspected of causing cancer. May cause damage to auditory system through prolonged or repeated exposure. May cause skin sensitization.

NOTE TO PHYSICIAN: Treatment of overexposure should be directed at the control of symptoms and the clinical condition. Suspected cancer causing agent. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

Section 5 ~ Firefighting Measures

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, foam, and water spray or fog.

UNSUITABLE EXTINGUISHING MEDIA: Water jets or streams which may spread flames.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Shut off all sources of ignition. Use water spray to disperse vapor and cool fire exposed containers. Prevent run off from entering streams, sewers, or drinking water supply.

UNUSUAL FIRE AND EXPLOSION HAZARDS: EXTREMELY FLAMMABLE. Pressurized container. Exposure to temperatures above 120 °F may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition. Vapors are heavier than air and can accumulate in low areas. Vapors may travel considerable distance to a source of ignition and flash back. Exposure to ignition sources can ignite vapors, causing a flash fire.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, various hydrocarbons.

Section 6 ~ Accidental Release Measures

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Eliminate all sources of ignition. Clean up using cloth or absorbent material. Dispose of product-containing wiping cloth or absorbent paper in suitable manner.

WASTE DISPOSAL: Dispose of in accordance with local, state, and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

Section 7 ~ Handling and Storage

HANDLING AND STORAGE: Do not use or store near heat, open flames, or other sources of ignition. Wear proper personal protective equipment when using this product. Avoid contact with skin, eyes and clothing. Do not inhale mist or vapor. Do not use or store with strong oxidizers. Protect from sunlight. Store in a well ventilated area. Do not expose to temperatures exceeding 50 °C/122 °F. Pressurized container: Do not pierce or burn, even after use. Store in a cool, dry area.

OTHER PRECAUTIONS: Keep out of the reach of children. Aspiration hazard if swallowed. Can enter lungs and cause damage. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not taste or swallow. Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health.

INCOMPATIBILITY: Strong alkalis, strong oxidizing agents, some plastics, rubber. Strong acids. Strong reducing agents.

Section 8 ~ Exposure Controls/Personal Protection

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Xylene	100 ppm	100 ppm
Acetone	1000 ppm	250 ppm
Diethylene glycol n-butyl ether	Not Established	10 ppm (inhalable fraction and vapor)
Propane	1000 ppm	1000 ppm
n-Butane	Not Established	1000 ppm
d-Limonene	Not Established	Not Established

ENGINEERING CONTROLS / VENTILATION: Local ventilation/exhaust preferred. Material is flammable and heavier than air. Material may concentrate in low lying areas.

RESPIRATORY PROTECTION: Not required with normal use. Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses/goggles, chemical resistant gloves, and protective clothing.

ADDITIONAL MEASURES: No smoking or open flames. Wear protective clothing to prevent repeated or prolonged contact with product. If clothing becomes contaminated, immediately remove and wash. Contaminated work clothing must not be allowed out of the workplace. Avoid contact with skin or eyes and avoid breathing vapors. Wash hands after use.

Section 9 ~ Physical and Chemical Properties

APPEARANCE: Viscous, light tan spray

ODOR: Acetone

ODOR THRESHOLD: N/D

pH: N/D

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: N/D

FLASH POINT: N/D

EVAPORATION RATE: N/D

FLAMMABILITY(solid/gas): Extremely Flammable Aerosol

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

LOWER FLAMMABILITY LIMIT: N/D

UPPER FLAMMABILITY LIMIT: N/D

EXPLOSIVE LIMIT LOWER (%): N/D

EXPLOSIVE LIMIT UPPER (%): N/D

VAPOR PRESSURE (mm Hg): N/D

VAPOR DENSITY (AIR=1): N/D

RELATIVE DENSITY (H₂O=1): 0.86-0.91

SOLUBILITY(IES): N/D

PARTITION COEFFICIENT: n-OCTANOL/WATER (KOW): N/D

AUTOIGNITION TEMPERATURE: N/D

DECOMPOSITION TEMPERATURE: N/D

VISCOSITY: N/D

Section 10 ~ Stability and Reactivity

REACTIVITY: Certain plastics, rubber and coatings.

CHEMICAL STABILITY: Stable under normal storage conditions.

POSSIBLE HAZARDOUS REACTIONS: None known.

CONDITIONS TO AVOID: Temperatures greater than 122 °F and sources of ignition. Avoid incompatibles.

INCOMPATIBLE MATERIALS: Strong alkalis, strong oxidizing agents, some plastics, rubber. Strong acids. Strong reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Stable under normal storage conditions.

Section 11 ~ Toxicological Information

TOXICOLOGICAL INFORMATION: **Xylene** (1330-20-7) LD50 (Oral, Rat) 4000 mg/kg; LC50 (Inhalation, Vapor, Mice) 5000 ppm. **Acetone** (67-64-1): LD50 (Oral, Rat) 5800 mg/kg; LD50 (Oral, Mouse) 3000 mg/kg; LD50 (Oral, Rabbit) 5340 mg/kg; LC50 (Inhalation, Rat, 8h) 50100 mg/m3; LC50 (Inhalation, Mouse, 4h) 44,000 mg/m3.

Propane (74-98-6): LC50 (Inhalation, Rat, 4h) 658 mg/L. **n-Butane** (106-97-8): LC50 (Inhalation, Rat, 4h) 30957 mg/m3. **d-Limonene** (5989-27-5): LD50 (Oral, Rat) 4400 mg/kg; LD50 (Mouse) 5600 mg/kg; LD50 (Dermal, Rabbit) 5000 mg/kg.

ROUTES OF ENTRY: Eyes, Inhalation, Skin, and ingestion.

EYES: Causes irritation. May cause conjunctivitis with possible corneal injury. May cause irritation, pain, redness, tearing, swelling.

INGESTION: Not an expected route of exposure. May cause gastrointestinal irritation, nausea, diarrhea, vomiting, abdominal cramps.

INHALATION: May cause respiratory tract irritation, dizziness, headaches, nausea, unconsciousness, central nervous system (CNS) depression.

SKIN: Causes irritation, redness, itching, and pain.

MEDICAL CONDITION AGGRAVATED: Pre-existing conditions of the skin, liver, kidneys, and central nervous system (CNS).

ACUTE HEALTH HAZARDS: Causes skin and serious eye irritation. May be fatal if swallowed and enters airways.

CHRONIC HEALTH HAZARDS: Suspected of causing cancer. May cause damage to auditory system through prolonged or repeated exposure. May cause skin sensitization.

CARCINOGENICITY: OSHA: Not classified. **ACGIH:** A4 - Not Human/animal **NTP:** No **IARC:** 3 - Not classifiable **OTHER:** CA Prop 65

Section 12 ~ Ecological Information

ECOTOXICITY: Toxic to aquatic life with long lasting effects. **Acetone** (67-64-1): LC50 (Oncorhynchus mykiss, 96h) 5540 mg/L; EC50 (Daphnia magna, 48h) 6100 mg/L; EC50 (Selenastrum quadricauda, 8d) 7500 mg/L; EC50 (Pseudomonas putida, 16h) 1700 mg/L. **Diethylene glycol n-butyl ether** (112-34-5): LC50 (Lepomis macrochirus, 96h) 1,300 mg/L; LC50 (Pseudomonas putida, 16h) 1,170 mg/L; EC50 (Daphnia magna, 48h) > 1000 mg/L; EC50 (Scenedesmus sp., 72h) > 100 mg/L. **d-Limonene** (5989-27-5): EC50 (Pimephales promelas, 96h) 688 µg/L; EC50 (Daphnia magna, 48h) 421 µg/L.

PERSISTENCE AND DEGRADABILITY: Component or components of this product are biodegradable.

BIOACCUMULATIVE POTENTIAL: Component or components of this product is not expected to bioaccumulate.

MOBILITY IN SOIL: This product is mobile in soil.

OTHER ADVERSE EFFECTS: None known.

Section 13 ~ Disposal Considerations

WASTE DISPOSAL: Dispose of in accordance with local, state, and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

Section 14 ~ Transportation Information

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammable.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

ENVIRONMENTAL HAZARDS WATER: N/A

Section 15 ~ Regulatory Information

TSCA STATUS: All chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Xylenes (1330-20-7) Reportable Quantity = 100 pounds. **Acetone** (67-64-1) Reportable Quantity = 5,000 pounds. **Ethyl benzene** (100-41-4) Reportable Quantity = 1000 pounds. **Cumene** (98-82-8) Reportable Quantity = 5,000 pounds.

SARA 311/312 HAZARD CATEGORIES: Physical & health hazards.

SARA 313 REPORTABLE INGREDIENTS: Xylenes (1330-20-7). **Ethyl benzene** (100-41-4). **Cumene** (98-82-8).

CLEAN WATER ACT: **Acetone** (67-64-1) is a hazardous substance. **Ethyl benzene** (100-41-1) is a hazardous substance. **Cumene** (98-82-8) is a hazardous substance.

STATE REGULATIONS: **California Proposition 65: WARNING:** This product can expose you to chemicals including **Ethyl benzene**, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov. **Xylene** (1330-20-7): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, DE, ID, ME, MA, MN, NJ, NY, PA, RI, WA. **Acetone** (67-64-1): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, DE, ID, ME, MA, MN, NJ, PA, RI, WA. **Diethylene glycol n-butyl ether (DB)** (112-34-5): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: PA, NJ.

INTERNATIONAL REGULATIONS: Listed or exempt from listing/notification on the following chemical inventories: Domestic Substances List and/or Non-domestic Substances List (DSL/NDL, Canada).

VOLATILE ORGANIC COMPOUNDS (VOC): 50%

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	3	*3	4= Severe
FLAMMABILITY	3	3	3= Serious
REACTIVITY	0	0	2= Moderate
OTHER	None		1= Slight
PERSONAL PROTECTION		C	0= Minimal

Disclaimer: Kayline Company, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and -may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet