



K150 DIAMITE SL

*100% Solid Epoxy Cement
Seal & Patch*

Flooring

Diamite SL is an epoxy system used to restore worn and eroded floors to their original condition and protect them from future deterioration. **Diamite SL** may be applied on any physically sound, clean, and dry substrate including concrete, brick, terrazzo, marble, metal or wood. It may also be used to improve floor tolerances and reduce surface imperfections. It is completely immune to the corrosive action of acids and alkalis in concentrations normally found in contact with floor surfaces.

USES:

Food Processing Plants, Bakeries, Kitchens, Cafeterias, Slaughterhouses, Supermarkets, Penitentiaries, Schools, Universities, Hospitals, Manufacturing Plants, Chemical Processing Plants, Laboratories, Morgues, Poultry Plants, Breweries & Bottling Plants

FEATURES:

- * Contains No Volatile Solvents Permitting Interior Applications With Virtually No Fire Hazard Or Toxic Odor
- * USDA Approved As An Acceptable Floor Resurfacing Compound In Processing & Storage Areas For Meat & Poultry Food Products
- * 100% Solids Epoxy System Complies With VOC Regulations
- * Pourable Self-Leveling Consistency Is Easy To Place Without Requiring Special Tools Or Equipment
- * Rapid Cure Time Drastically Reduces Operational Downtime & Allows For Exposure To Light Traffic In Less Than 16 Hours At 75°F
- * Varying Application Thicknesses Save Labor Installation Costs By Eliminating The Need For Workmen To Return To The Job Site For Multiple Applications
- * Dense Surface Is Easy To Clean & Resists Mildew & Bacteria Growth
- * Epoxy & Natural Aggregate System Is Highly Resistant To Impact. Does Not Chip, Or Peel
- * Produces A Seamless & Slip Resistant Flooring Surface While Offering Excellent Protection Against Chemical Attack